



YDP20MH

PORTABLE DIESEL FIRE PUMP

- NON-CORROSIVE FEATURES
- ALUMINIUM ROLL OVER FRAME
- 2" (50mm) SUCTION HOSE WITH FOOT VALVE AND STRAINER
- STORZ MALE AND FEMALE QUICK RELEASE CONNECTORS

MODEL	YDP20MH	
ENGINE	YANMAR	
	L48 TC	
TYPE	Vertical 4-cycle, air cooled diesel engine	
DISPLACEMENT	cc cu.in	211 (12.88)
OUTPUT MAX.	HP/RPM	4.7/3600
OUTPUT CONT.	HP/RPM	4.2/3600
STARTING SYSTEM	RECOIL	
FUEL OIL TANK CAPACITY	2.5 (0.7)	
	LTS (U.S. GAL)	
PUMP	YDP20 MH	
TYPE	Self-priming centrifugal pump	
SUC. & DISCHARGE DIA	mm (in)	50 (2)
MAX. TOTAL HEAD	m (ft.)	26 (85.3)
SUCTION LIFT	m (ft.)	8 (26.2)
MAX. CAPACITY LTS (U.S.GAL) /min	500 (132.1)	
UNIT	YDP20MH	
DIMENSIONS	L X W X H mm (in.)	515X430X510 (20.3X16.9X20.1)
DRY WEIGHT	40 (88.2)	



BRITTON MARINE (AUSTRALIA) PTY LTD

TEL: 61-2-95254172 FAX: 61-2-95311143

EMAIL: brittonmarine@bigpond.com